

Retrofitable Low-pressure EGR for Diesel NOx & PM Control

CT DEP Clean Diesel Fuels & Technology Forum

Alex Gorel

Hartford, CT August 17, 2005



Low-pressure EGR was developed by STT Emtec, AB in cooperation with Johnson Matthey, Inc.

The system is being marketed under the EGRT™ trademark



Underlying Operating Principals

Formation of NO is affected through peak combustion temp and O₂ content

Formation of NO₂ is affected through content of NO & O₂ in the exhaust

EGR controls both, NO & NO₂



EGRT System Layout

Intercooler


Air intake filter

EGR throttle

Secondary filter


Valve





ECU





Secondary Filter



Cooler





Important EGRT Features

Re-circulates Clean Cooled Exhaust Gas

Excellent Transient Controllability

OBD System

Engine and DPF Protection

Built-in Memory with Datalogging Capability and Failure Code Retention



EGRT Is CARB Verified as a Level III
Retrofit Technology
Reducing
PM >85% & NOx >40%



Verified Emissions Control Group

On-road Applications Of The Following Engine Models:

International DT-466
Cummins ISB, ISC, ISM, and ISL
DDC S50 and S60

New Models Are Being Added Per Customer Requests



EGRT Applicability

4-stroke, turbo, non-EGR engines


Engine-out PM is 0.01 < PM < 0.1 gm/bhp-hr


Duty cycle: 260°C for more than 40% of time

Refer to CARB website for complete details




Example of Connecticut School Bus Duty Cycle Suitability for use of EGRT






Hartford (Typical Case Scenario/Inner City Travel) International Bus, T444E Rear Engine, 195 Hp




New Haven School Bus# 270, Worst Case Scenario International Bus, T444E Front Engine, 195Hp





EGRT Controls NO₂ Production

(Scania 9L Euro-3 Bus Engine, ETC)



EGRT Summary

Well proven with over 2400 systems installed worldwide

CARB verified

Commercially available

Requires ULSF

Installation takes ∼ 16 man-hr



CCT®

Catalytic Combustion Technology

For DPF Active

Regeneration Control




CCT Provides
Reliable Mean of Regeneration
to
Low-temperature
and/or
High-PM applications

Currently Available on an Experimental Basis




CCT System Layout





An Example of a Regeneration Event





Contact Information:

Mr. Alex Gorel

E-mail: Alex.Gorel@STTEmtec.com

Phone: (908) 720-9770

Thank you for your attention

